(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 18 September 2003 (18.09.2003)

PCT

(10) International Publication Number WO 03/077390 A1

(51) International Patent Classification⁷: HOLL 33/00 H01S 5/227,

(21) International Application Number: PCT/SEG

PCT/SE03/00387

7 March 2003 (07.03.2003)

(22) International Filing Date:

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0200750-8

13 March 2002 (13.03.2002) SE

(71) Applicant (for all designated States except US): OPTIL-LION AB [SE/SE]; Box 47646, S-117 94 Stockholm (SE).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): STOLTZ, Björn [SE/SE]; Birger Jarlsgatan 102A, S-114 20 Stockholm (SE). BENDZ, Eskil [SE/SE]; Vikingagatan 26, S-113 42 Stockholm (SE).
- (74) Agent: EHRNER & DELMAR PATENTBYRÅ AB; Box 103 16, S-100 55 Stockholm (SE).


- (81) Designated States inational): AE, AG, AL, AM, AT (utility model). AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model). CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model). EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR). OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR MANUFACTURING A PHOTONIC DEVICE AND A PHOTONIC DEVICE



(57) Abstract: The present invention relates to a photonic device having a first set of layers (22) including at least a first waveguide layer (3) arranged in a waveguide mesa (61). A cladding layer (7) is arranged on top of the waveguide mesa (61) and surrounding semiconductor material (1). A contact layer (8) is arranged on top of the cladding layer (7), and a metal contact (9, 80) is arranged on top of the contact layer (8). The cladding (7) and contact (8) layer are shaped in an etching process to have a mesa structure at least above the waveguide mesa (61). An insulating material (25, 82) is also applied around the mesa structure. Optionally a second photonic device having a second set of layers (31) including at least a second waveguide layer (33), may be coupled to the first photonic device in a light transmission direction thereof. The invention also relates to a method for manufacturing the photonic device.



WO 03/077390 A1